


Item code	Dimensions,mm					Hole Diameter ØD		Insert	Screw	Wrench	vveigni	
nom oodo	L	W	Т	Н	В	F	min	max	moort			Kg
HFAVR-029-3T13	63.5	3	13	36	20	12	29	34	HFPR30	HTMT525	ETL25	0.20
HFAVR-034-3T12			12				34	40				
HFAVR-034-3T16			16				34	40				
HFAVR-040-3T12			12				40	48				
HFAVR-040-3T16			16				40	48				
HFAVR-048-3T12			12 20				48 48	60				
HFAVR-048-3T20 HFAVR-060-3T12			12				60	75				
HFAVR-060-3T20			20				60	75				
HFAVR-075-3T12			12			13	75	100				
HFAVR-075-3T20			20				75	100				
HFAVR-100-3T20					18.5	-	100	140				
HFAVR-140-3T20					17		140	200				
HFAVR-200-3T20					14.5		200	800				
HFAVR-075-3T25	68.5	3	25	36	20	13	75	100				
HFAVR-100-3T25					18.5		100	140				
HFAVR-140-3T25					17		140	200				
HFAVR-200-3T25					14.5		200	800				
HFAVR-029-4T13	63.5	4	13	36	20	12	29	34	HFPR40	HTMT525	ETL25	0.40
HFAVR-034-4T12		·	12				34	40	GRIP40			
HFAVR-034-4T16			16				34	40				
HFAVR-040-4T12			12				40	48				
HFAVR-040-4T20			20				40	48				
HFAVR-048-4T12			12	-		14	48	60				
HFAVR-048-4T20			20				48	60				
HFAVR-060-4T12			12				60	75				
HFAVR-060-4T20			20				60	75				
HFAVR-075-4T12			12				75	100				
HFAVR-075-4T20			20				75	100				
HFAVR-100-4T20					18.5		100	140				
HFAVR-140-4T20					17		140	200				
HFAVR-200-4T20					14.5		200	800				
HFAVR-075-4T25	68.5	4	25	36	20	14	75	100				
HFAVR-100-4T25					18.5		100	140				
HFAVR-140-4T25					17		140	200				
HFAVR-200-4T25					14.5		200	800				

<sup>※</sup>訂購刀座請參考140頁Please refer to page 140 for holder.

## 斯**朗**開帽/J FACE GROOVING TOOLHOLDERS







Item code		Dime	ensions	,mm		Adapter	Screw	Wrench	Weight
	Н	В	L	H1	Т	Adaptor			Kg
HFAPR-2025K-12	20	25	125	42	15	HFAVR	MS6022E	PL50	0.68
HFAPR-2525K-12	25	25	125	42	15				0.78

被切削材 Workpiece material	Steel 鋼	Р	•	
	Stainless steel 不銹鋼	М	•	
	Cast iron 鑄鐵	K	•	•
	Non-ferrous metal 非鐵金屬	Ν		•

	Description		GRADI	Dimensions,mm				
Insert Shape			Coated 塗層 Uncoated 無塗層					
			IC354	IC20	W	L	М	Re
ı ∠-Re	HFPR	3003	•	•	3	19	2.1	0.3
≥ DE		4004	•	•	4	19	2.8	0.4
Re	HFPR	3015			3	19	2.1	1.5
≥ L L		4020			4	19	2.8	2.0